



GU24 T2 - T3 SPIRAL & GU24 COVERED CFL

GU24 Base T2 Super Mini Spiral

Nominal Wattage	Overdrive Model #	Item Description & CCT	Initial Lumen	Average Rated Life (Hrs.)	Diameter (Inches/mm)	Length/ (Inches/mm)	Pack Inner/ Master	Item #
13	13W/ODSGU	13W T2 Super Mini Spiral GU24 Base - Soft White	800	10,000	1.8 / 46	3.4 / 86	25/50	078
13	13W/ODSGU/35K	13W T2 Super Mini Spiral GU24 Base - White	800	10,000	1.8 / 46	3.4 / 86	25/50	088
13	13W/ODSGU/41K	13W T2 Super Mini Spiral GU24 Base - Cool White	800	10,000	1.8 / 46	3.4 / 86	25/50	079
18	18W/ODT2SGU	18W T2 Super Mini Spiral GU24 Base - Soft White	1,200	10,000	2.1 / 54	3.8 / 97	25/50	191
18	18W/ODT2SGU/41K	18W T2 Super Mini Spiral GU24 Base - Cool White	1,200	10,000	2.1 / 54	3.8 / 97	25/50	192
23	23W/ODT2SGU	23W T2 Super Mini Spiral GU24 Base - Soft White	1,600	10,000	2.1 / 54	4.2 / 107	25/50	194
23	23W/ODT2SGU/41K	23W T2 Super Mini Spiral GU24 Base - Cool White	1,600	10,000	2.1 / 54	4.2 / 107	25/50	195
23	23W/ODT2SGU/50K	23W T2 Super Mini Spiral GU24 Base - Natural DL	1,600	10,000	2.1 / 54	4.2 / 107	25/50	196

GU24 Base T3 Mini Spiral

18	18W/ODSGU/41K	18W T3 Mini Spiral GU24 Base - Cool White	1,200	10,000	2.1 / 54	4.3 / 108	25/50	082
26	26W/ODSGU	26W T3 Mini Spiral GU24 Base - Soft White	1,610	10,000	2.1 / 54	5.2 / 128	25/50	084
26	26W/ODSGU/41K	26W T3 Mini Spiral GU24 Base - Cool White	1,725	10,000	2.1 / 54	5.2 / 128	25/50	085
26	26W/ODSGU/50K	26W T3 Mini Spiral GU24 Base - Natural DL	1,700	10,000	2.1 / 54	5.2 / 128	25/50	086

Applications



Features

- 10,000 hour average rated life reduces relamping & related costs
- Rare earth tri-phosphor with 80 plus CRI for better performance
- High Luminous Efficacy
- 75% Lower Power Consumption over incandescent bulbs
- Available in various color temperature
- Compact in Size and fits most applications

Notes

- Not Dimmable
- Available in other color temperature also (upon request)
- Dimension with + 0.1 inch tolerance
- Use not recommended for totally enclosed fixture

