



QUAD PLUG-IN CFL

2 Pin Quad (Double) Tube CFL - Suitable for Preheat Magnetic Ballast

Nominal Wattage	Overdrive Model #	Generic Designation	Item Description & CCT	Lamp Base	Initial Lumen	Average Rated Life (Hrs.)	Length/MOL (Inches/mm)	Pack Inner/Master	Item #
13	ODD13W/27K	CFQ13W/GX23/827	13W Quad CFL -2Pin-2700K	GX-23-2	860	10,000	4.7 / 120	25 / 100	012
13	ODD13W/35K	CFQ13W/GX23/835	13W Quad CFL -2Pin-3500K	GX-23-2	860	10,000	4.7 / 120	25 / 100	013
13	ODD13W/41K	CFQ13W/GX23/841	13W Quad CFL -2Pin-4100K	GX-23-2	860	10,000	4.7 / 120	25 / 100	014
18	ODD18W/27K	CFQ18W/G24d/827	18W Quad CFL -2Pin-2700K	G24d2	1,200	10,000	6.2 / 157	25 / 100	017
18	ODD18W/35K	CFQ18W/G24d/835	18W Quad CFL -2Pin-3500K	G24d2	1,200	10,000	6.2 / 157	25 / 100	018
18	ODD18W/41K	CFQ18W/G24d/841	18W Quad CFL -2Pin-4100K	G24d2	1,200	10,000	6.2 / 157	25 / 100	019
26	ODD26W/27K	CFQ26W/G24d/827	26W Quad CFL -2Pin-2700K	G24d3	1,800	10,000	7.0 / 178	25 / 100	022
26	ODD26W/35K	CFQ26W/G24d/835	26W Quad CFL -2Pin-3500K	G24d3	1,800	10,000	7.0 / 178	25 / 100	023
26	ODD26W/41K	CFQ26W/G24d/841	26W Quad CFL -2Pin-4100K	G24d3	1,800	10,000	7.0 / 178	25 / 100	024

4 Pin Quad (Double) Tube CFL - Suitable for Electronic Ballast

13	ODD13W/4P/27K	CFQ13W/G24q/827	13W Quad CFL -4Pin -2700K	G24q1	900	12,000	5.3 / 135	25 / 100	015
13	ODD13W/4P/35K	CFQ13W/G24q/835	13W Quad CFL -4Pin -3500K	G24q1	900	12,000	5.3 / 135	25 / 100	099
13	ODD13W/4P/41K	CFQ13W/G24q/841	13W Quad CFL -4Pin -4100K	G24q1	900	12,000	5.3 / 135	25 / 100	016
18	ODD18W/4P/27K	CFQ18W/G24q/827	18W Quad CFL -4Pin -2700K	G24q2	1,250	12,000	5.9 / 150	25 / 100	020
18	ODD18W/4P/35K	CFQ18W/G24q/835	18W Quad CFL -4Pin -3500K	G24q2	1,250	12,000	5.9 / 150	25 / 100	100
18	ODD18W/4P/41K	CFQ18W/G24q/841	18W Quad CFL -4Pin -4100K	G24q2	1,250	12,000	5.9 / 150	25 / 100	021
26	ODD26W/4P/27K	CFQ26W/G24q/827	26W Quad CFL -4Pin -2700K	G24q3	1,800	12,000	6.7 / 171	25 / 100	025
26	ODD26W/4P/35K	CFQ26W/G24q/835	26W Quad CFL -4Pin -3500K	G24q3	1,800	12,000	6.7 / 171	25 / 100	101
26	ODD26W/4P/41K	CFQ26W/G24q/841	26W Quad CFL -4Pin -4100K	G24q3	1,800	12,000	6.7 / 171	25 / 100	026

Applications



WALL
SCONE



CEILING



TABLE/ FLOOR
LAMPS



READING
LAMP



RECESSED
CANS



OUTDOOR
COVERED

Features

- 10,000 to 12,000 hour average rated life reduces relamping & related costs
- Rare earth tri-phosphor with 80 plus CRI for better performance
- High Luminous Efficacy
- 75% Lower Power Consumption over incandescent bulbs
- Available in various color temperature
- Compact Size

Notes

- 4-Pin lamps are designed for Dimming & electronic applications
- Minimum Starting Temperature is also very much dependent on ballast.
- Available in other color temperature also (upon request)
- Equipment manufacturer are suggested to consult ANSI or IEC standard for maximum allowable dimensions & temperature for the optimum performance of the product.