



TRIPLE PLUG-IN CFL

4 Pin (Triple) Tube CFL - Suitable for Electronic Ballast

Nominal Wattage	Overdrive Model #	Generic Designation	Item Description & CCT	Lamp Base	Initial Lumen	Average Rated Life (Hrs.)	Length/MOL (Inches/mm)	Pack Inner/Master	Item #
26	ODT26W/4P/27K	CFTR26W/GX24q/827	26W Triple CFL-4pin-2700K	GX24q3	1,800	12,000	5.0 / 126	25/100	108
26	ODT26W/4P/35K	CFTR26W/GX24q/835	26W Triple CFL-4pin-3500K	GX24q3	1,800	12,000	5.0 / 126	25/100	042
26	ODT26W/4P/41K	CFTR26W/GX24q/841	26W Triple CFL-4pin-4100K	GX24q3	1,800	12,000	5.0 / 126	25/100	043
32	ODT32W/4P/27K	CFTR32W/GX24q/827	32W Triple CFL-4pin-2700K	GX24q3	2,400	12,000	5.6 / 142	25/100	109
32	ODT32W/4P/35K	CFTR32W/GX24q/835	32W Triple CFL-4pin-3500K	GX24q3	2,400	12,000	5.6 / 142	25/100	045
32	ODT32W/4P/41K	CFTR32W/GX24q/841	32W Triple CFL-4pin-4100K	GX24q3	2,400	12,000	5.6 / 142	25/100	046
42	ODT42W/4P/27K	CFTR42W/GX24q/827	42W Triple CFL-4pin-2700K	GX24q4	3,200	12,000	6.4 / 161	25/100	110
42	ODT42W/4P/35K	CFTR42W/GX24q/835	42W Triple CFL-4pin-3500K	GX24q4	3,200	12,000	6.4 / 161	25/100	048
42	ODT42W/4P/41K	CFTR42W/GX24q/841	42W Triple CFL-4pin-4100K	GX24q4	3,200	12,000	6.4 / 161	25/100	049
57	ODT57W/4P/27K	CFTR57W/GX24q/827	57W Triple CFL-4pin-2700K	GX24q5	4,300	12,000	7.8 / 198	25/50	147
57	ODT57W/4P/30K	CFTR57W/GX24q/830	57W Triple CFL-4pin-3000K	GX24q5	4,300	12,000	7.8 / 198	25/50	148
57	ODT57W/4P/35K	CFTR57W/GX24q/835	57W Triple CFL-4pin-3500K	GX24q5	4,300	12,000	7.8 / 198	25/50	149
57	ODT57W/4P/41K	CFTR57W/GX24q/841	57W Triple CFL-4pin-4100K	GX24q5	4,300	12,000	7.8 / 198	25/50	150
70	ODT70W/4P/27K	CFTR70W/GX24q/827	70W Triple CFL-4pin-2700K	GX24q6	5,200	12,000	9.3 / 236	25/50	151
70	ODT70W/4P/30K	CFTR70W/GX24q/830	70W Triple CFL-4pin-3000K	GX24q6	5,200	12,000	9.3 / 236	25/50	152
70	ODT70W/4P/35K	CFTR70W/GX24q/835	70W Triple CFL-4pin-3500K	GX24q6	5,200	12,000	9.3 / 236	25/50	153
70	ODT70W/4P/41K	CFTR70W/GX24q/841	70W Triple CFL-4pin-4100K	GX24q6	5,200	12,000	9.3 / 236	25/50	154

Applications



WALL
SCONE



CEILING



TABLE/ FLOOR
LAMPS



READING
LAMP



RECESSED
CANS



OUTDOOR
COVERED

Features

- 10,000 to 12,000 hour average rated life reduces relamping & related costs
- Rare earth tri-phosphor with 80 plus CRI for better performance
- High Luminous Efficacy
- 75% Lower Power Consumption over incandescent bulbs
- Available in various color temperature
- Compact Size

Notes

- 4-Pin lamps are designed for Dimming & electronic applications
- Minimum Starting Temperature is also very much dependent on ballast.
- Available in other color temperature also (upon request)
- Equipment manufacturer are suggested to consult ANSI or IEC standard for maximum allowable dimensions & temperature for the optimum performance of the product.

