

# TWIN PLUG-IN CFL



## 2 Pin Twin (Single) Tube CFL - Suitable for Preheat Magnetic Ballast

Nominal Wattage	Overdrive Model #	Generic Description	Item Description & CCT	Base Type	Initial Lumen	Average Rated Life(Hrs.)	Length (Inch/mm)	Pack Inner/Master	Item #
7	ODS7W/27K	CFT7W/G23/827	7W Twin CFL - 2Pin - 2700K	G23	400	10,000	5.3 / 135	25 / 100	002
9	ODS9W/27K	CFT9W/G23/827	9W Twin CFL - 2Pin - 2700K	G23	600	10,000	6.6 / 167	25 / 100	004
9	ODS9W/41K	CFT9W/G23/841	9W Twin CFL - 2Pin - 4100K	G23	600	10,000	6.6 / 167	25 / 100	005
13	ODS13W/27K	CFT13W/GX23/827	13W Twin CFL - 2Pin - 2700K	GX23	825	10,000	7.0 / 178	25 / 100	006

## 4 Pin Twin (Single) Tube CFL - Suitable for Electronic Ballast

Nominal Wattage	Overdrive Model #	Generic Description	Item Description & CCT	Base Type	Initial Lumen	Average Rated Life(Hrs.)	Length (Inch/mm)	Pack Inner/Master	Item #
13	ODS13W/4P/27K	CFT13W/2GX7/827	13W Twin CFL - 4Pin 2700K	2GX7	840	12,000	6.3 / 160	25 / 100	010



### Features

- 10,000 to 12,000 hours average rated life reduces relamping & related costs
- Rare earth tri-phosphor with 80 plus CRI for better performance
- High Luminous Efficacy
- 75% Lower Power Consumption over incandescent bulbs
- Available in various color temperatures
- Compact Size

### Notes

- 4-Pin lamps are designed for dimming & electronic applications
- Minimum Starting Temperature is also very much dependent on ballast.
- Available in various color temperatures (upon request)
- Equipment manufacturers should consult ANSI or IEC standard for maximum allowable dimensions & temperature for the optimum performance of the product.