



**6W LED CRI 90 Globe G25  
Dimmable - 2700K**

**Item # 687**  
**L6HG25DIM/27K**



<b>1 LAMP SPECIFICATION</b>			
1-1	Lamp Type	LED GLOBE	
1-2	Dimmable (Y/N)	YES	
1-3	Base	E26	
1-4	Lamp Finish/Type	GLOBE	
1-5	Lamp Wattage	6W	
1-6	Wattage Comparison (FC on Floor)	40W G25	
1-7	Rated Average Life (hours) L70	25,000	
1-8	Reliable Operating Temperature	-4F to 113F	
<b>2 Photometric Characteristics</b>			
2-1	Initial Lumens	390	
2-2	Centre Beam Candle Power (Cd)	NA	
2-3	Beam Angle (50% I Max) in Degree	175	
2-4	Beam Angle (10% I Max) in Degree	NA	
2-5	Initial Lumens per Watt	65	
2-6	Color Temperature	2700K	
2-7	Color Rendering Index (CRI)	90	
<b>3 Electrical Characteristics</b>			
3-1	Input Line Voltage/Frequency	120V 60Hz	3-2 Power Factor 0.92
3-3	Lamp rated Wattage	6W	3-4 Input Line Current 55 mA
3-5	Total Harmonic Distortion	33%	3-6 Dimming Range in % Full
<b>4 Dimensional Characteristics</b>			
4-1	Nominal Length (Inches/mm)	4.25" / 108 mm	4-2 Diameter 3.15" / 80 mm
<b>5 Product Information</b>			
5-1	Description	6W LED CRI 90 Globe G25 Dimmable - 2700K	
5-2	Primary Application	Household Use, Office & Commercial	
5-3	Warranty	5 Years from date of purchase	
5-4	TCLP Compliant	YES	5-6 RoHS Compliant YES
5-5	Energy Star or LM79 (Y/N)	ES	5-8 UL / FCC YES
<b>6 PACKING DETAILS</b>			
6-1	Color Box Size (inch)	1x1 3.2 X 3.5 X 4.6	6-2 Inner Carton Size (inch) 1x1 NA
6-3	Master Carton Size (inch)	1x12 13.82 X 10.43 X 5.94	6-4 Gross Weight / Net Weight (lbs) 3.59/2.01
02/2017© Overdrive For more information visit <a href="http://www.overdrive-lighting.com">www.overdrive-lighting.com</a>			
Note: This data sheet is not controlled copy & is subject to change without notice. Standard Tolerances apply on data given above.			