



11W LED High CRI PAR30 Long Neck Flood Dimmable - 5000K

Item # 693

L11HPAR30LNDIM/FL/50K

1 LAMP SPECIFICATION

1-1 Lamp Type	LED 90CRI PAR30
1-2 Dimmable (Y/N)	YES
1-3 Base	E26
1-4 Lamp Finish/Type	PAR30
1-5 Lamp Wattage	11W
1-6 Wattage Comparison (FC on Floor)	75W Incand
1-7 Rated Average Life (hours) L70	25,000
1-9 Reliable Operating Temperature	-4F to 113F



2 Photometric Characteristics

2-1 Initial Lumens	900
2-2 Centre Beam Candle Power (Cd)	1350
2-3 Beam Angle (50% I Max) in Degree	40(Flood)
2-4 Beam Angle (10% I Max) in Degree	N/A
2-5 Initial Lumens per Watt	82
2-6 Color Temperature	5000K
2-7 Color Rendering Index (CRI)	90

3 Electrical Characteristics

3-1 Input Line Voltage/Frequency	120V 60 Hz	3-2 Power Factor	0.94
3-3 Lamp rated Wattage	11W	3-4 Input Line Current	110 mA
3-5 Total Harmonic Distortion	25%	3-6 Dimming Range in %	Full

4 Dimensional Characteristics

4-1 Nominal Length (Inches/mm)	4.57"/116 mm	4-2 Diameter	3.74"/95mm
--------------------------------	--------------	--------------	------------

5 Product Information

5-1 Description	11W LED High CRI PAR30 Long Neck Flood Dimmable - 5000K		
5-2 Primary Application	Household Use, Office & Commercial		
5-3 Warranty	5 Years from date of purchase		
5-4 TCLP Compliant	YES	5-6 RoHS Compliant	YES
5-5 Energy Star or LM79 (Y/N)	No	5-8 UL / FCC	YES

6 PACKING DETAILS

6-1 Color Box Size (Inches)	1x1	3.9 x 3.9 x 4.9	6-2 Inner Carton Size (Inches)	
6-3 Master Carton Size (Inches)	1x12	16.65 x 12.60 x 6.22	6-4 Gross Weight / Net Weight (lbs)	5.78 / 3.13

04/2021© Overdrive For more information visit www.overdrive-lighting.com

Note: This data sheet is not controlled copy & is subject to change without notice. Standard Tolerances apply on data given above.